



Restek Air

Sampling with Thermal Desorption Tubes Has Never Been Easier

Restek Offers Options for Every Application

- Grab and time-integrated sampling
- Single-tube pump or multi-tube sequential sampler
- Manual or battery-operated power



RESTEK

Pure Chromatography

www.restek.com



**CHROMATOGRAPHIC
SPECIALTIES INC.**

www.chromspec.com

1-800-267-8103 • sales@chromspec.com • tech@chromspec.com



ACTI-VOC Low-Flow TD Sampling Pump

- Robust, low-flow pump optimized for sampling volatile organic compounds (VOCs) onto thermal desorption (TD) sorbent tubes.
- Small, lightweight, easy to use, and intrinsically safe—ideal for personal monitoring and a wide range of other air and gas sampling applications.
- Compatible with any TD tube (up to a max flow of 350 mL/min); automatically compensates for different impedances, ensuring constant flow rates with any sorbent packing.
- Allows constant flow sampling from 20–200 mL/min and constant pressure sampling from 1–350 mL/min.
- Easy to calibrate via a simple screw-operated flow adjustment.
- Rechargeable NiMH battery ensures stable performance for over 8 hours.
- Supplied in a convenient carrying case with charger (100–240 V) and accessories.

Description	qty.	cat.#
ACTI-VOC Low-Flow TD Sampling Pump	ea.	26463

MTS-32 TD Multiple Tube Sequential Sampler

- Allows sequential sampling of up to 32 thermal desorption tubes (3.5" each).
- Worry-free, independent operation lets you get more done—simply set up the unit in the field for extended sampling, then retrieve it at the end of the sampling period.
- Reliably collect accurate samples; diffusion-locking technology prevents sample losses or the ingress of contaminants.
- Easy to use and portable; use almost anywhere to sample pollutants in ambient air or continuously monitor industrial emissions.
- Quality construction made of low-outgassing materials; includes built-in fan that refreshes chamber air to ensure representative sampling.
- Optional accessories let you power unit by either 110–240 V power or a battery (will operate 40 hours on battery).

Description	qty.	cat.#
MTS-32 TD Multiple Tube Sequential Sampler	ea.	26464

Accessories for MTS-32 TD Multiple Tube Sequential Sampler	qty.	cat.#
Power Supply for MTS-32 TD Multiple Tube Sequential Sampler (use instead of battery)	ea.	26465
12 V Battery for MTS-32 TD Multiple Tube Sequential Sampler (use in place of power supply)	ea.	26467
Mains Charger for 12 V Battery for MTS-32 TD Multiple Tube Sequential Sampler (use to recharge battery)	ea.	26466

Easy-VOC Grab Sampler

- Perfect for fast and simple grab sampling of small air volumes (50–500 mL) directly into sorbent tubes.*
- Easy, instant sample collection with no complicated pumps to calibrate or maintain.
- Convenient to use anywhere, just attach a sorbent tube to the end of the handheld unit and draw a sample directly into the tube.
- Accurate, reproducible sampling is assured as this device regulates flow rate independent of the force used to draw the air sample.
- Fits 1/4" and 6 mm outer diameter sorbent tubes.

Description	qty.	cat.#
Easy-VOC Grab Sampler	ea.	26468

*Sorbent tubes not included.



also available

Alicat and Defender flow calibrators make it easy to accurately set and confirm proper flow rates.



Note: Power supplies and sampling pump sold separately.



RESTEK
Pure Chromatography

Restek® patents and trademarks are the property of Restek Corporation. (See www.restek.com/Patents-Trademarks for full list.) Other trademarks in Restek® literature or on its website are the property of their respective owners. Restek® registered trademarks are registered in the U.S. and may also be registered in other countries.

© 2015 Restek Corporation. All rights reserved. Printed in the U.S.A.

www.restek.com



Lit. Cat.# EVSS2225-UNV



**CHROMATOGRAPHIC
SPECIALTIES INC.**
www.chromspec.com

1-800-267-8103 • sales@chromspec.com • tech@chromspec.com

